

ATV 22 - Filter fans 58 m3/hr



Features	Unit	ATV2000U_MPX	ATV2200U_MPX	ATV2201U_MPX	ATV2224U_MPX	ATV2248U_MPX
Air flow rate (free blow)	m3/h	-	58(64)		58	
Air flow rate with exit filter	m3/h	-	43(48)		43	
Power supply	V/Hz	-	230 / 50-60	115 / 50-60	24DC	48DC
Dimensions HxWxD	mm	150x150x37		150x150x86		
Power consumption	W	-	22 (21)		9	13
Current consumption	A	-	0.14(0.12)	0.26(0.24)	0.37	0.27
Overcurrent protection	-	-	impedance			
Electrical connection	-	-	3-poles spring terminals *		2-poles spring terminals *	
Duty cycle	-	-	100%			
Operating temperature	°C (°F)	-10 / +70 (+14/+158)				
Protection degree / Class	-	IP54	IP54 / Classe I			
Noise level	dB(A)	-	43 (49)		45	
Flow direction	-	-	reversible, default factory setting outside-in			
Bearing	-	-	ball			
Filter mat EN779	-	G3				
Service life (at 40°C)	hr	-	50 000			
Material	-	ABS UL94V-0 color RAL7035				
Wall thickness	mm	1.2 - 2.4				
Gasket	-	foam seal gasket				
Weight (with packaging)	kg	0.18(0.23)	0.76(0.83)		0.48(0.55)	
Package dimensions H x W x D	mm	165x165x45		165x165x90		
Mounting	-	fast clip-on				
Conformity/Certifications	-	CE				

* 0.5-2.5mm²

Versions				
UL-code ending			U	
EMC-code ending			X_MPX	
Accessories				
Filter mat, standard type			ATVF2_MPX	
Filter mat, high efficiency			ATVF2X_MPX	
Thermostat 0-60°C, NO contact	-		THV2_MPX	
Hood for IP56			HPS150U	

