

ATV 43 - ATV 44 - Filter fans 255-410 m3/hr



Features	Unit	ATV4000U_MPX	ATV4300U_MPX	ATV4301U_MPX	ATV4324U_MPX	ATV4348U_MPX	ATV4400U_MPX	ATV4401U_MPX
Air flow rate (free blow)	m3/h	-	255 (290)		255		410 (445)	
Air flow rate with exit filter	m3/h	-	202 (235)		202		280 (302)	
Power supply	V/Hz	-	230 / 50-60	115 / 50-60	24DC	48DC	230 / 50-60	115 / 50-60
Dimensions HxWxD	mm	250x250x38	250x250x128				250x250x136	
Power consumption	W	-	40 (38)		26	33	70 (90)	
Current consumption	A	-	0.17 (0.16)	0.34 (0.32)	1.08	0.68	0.40 (0.38)	0.80 (0.76)
Overcurrent protection	-	-	thermal		impedance		thermal	
Electrical connection	-	-	3-poles spring terminals *		2-poles spring terminals *		3-poles spring terminals *	
Duty cycle	-	-	100%					
Operating temperature	°C (°F)	-10 / +70 (+14/+158)						
Protection degree / Class	-	IP54	IP54 / Class I					
Noise level	dB(A)	-	53 (58)		61		65 (68)	
Flow direction	-	-	reversible, default factory setting outside-in					
Bearing	-	-	ball					
Filter mat EN779	-	G3						
Service life (at 40°C)	hr	-	50 000					
Material	-	ABS UL94V-0 color RAL7035						
Wall thickness	mm	1.2 - 2.4						
Gasket	-	schiuma						
Weight (with packaging)	kg	0.52(0.62)	1.72(1.92)		1.53(1.73)		2.74(2.94)	
Package dimensions H x W x D	mm	270x270x47	270x270x165					
Mounting	-	fast clip-on						
Conformity/Certifications	-	CE						

* 0.5-2.5mm²

Versions							
UL-code ending					U		
EMC-code ending					X_MPX		
Accessories							
Filter mat, standard type					ATVF4_MPX		
Filter mat, high efficiency					ATVF4X_MPX		
Thermostat 0-60°C, NO contact	-				THV2_MPX		
Hood for IP56		HPS250U (valid for codes atv4300-4301-4324-4348)			HPS325U (valid for codes atv4400-4401)		

