

ATV 54 - ATV 55 - Filter fans 550-700 m3/hr



Features	Unit	ATV5000U_MPX	ATV5400U_MPX	ATV5401U_MPX	ATV5500U_MPX
Air flow rate (free blow)	m3/h	-	550 (620)		700 (770)
Air flow rate with exit filter	m3/h	-	405 (450)		520 (575)
Power supply	V/Hz	-	230 / 50-60	115 / 50-60	230 / 50-60
Dimensions HxWxD	mm	325x325x42	325x325x140		325x325x154
Power consumption	W	-	70 (90)		130 (180)
Current consumption	A	-	0.40 (0.38)	0.80 (0.76)	0.55 (0.81)
Overcurrent protection	-	-	thermal		
Electrical connection	-	-	3-poles spring terminals *		3-poles spring terminals*
Duty cycle	-	-	100%		
Operating temperature	°C (°F)	-10 / +70 (+14/+158)			
Protection degree / Class	-	IP54	IP54 / Class I		
Noise level	dB(A)	-	65 (68)	72 (73)	
Flow direction	-	-	reversible, default factory setting outside-in		
Bearing	-	-	ball		
Filter mat EN779	-	-	G3		
Service life (at 40°C)	hr	-	50 000		
Material	-	ABS UL94V-0 color RAL7035			
Wall thickness	mm	1.2 - 2.4			
Gasket	-	foam seal gasket			
Weight (with packaging)	kg	0.90(1.04)	3.00(3.25)	3.55(3.80)	
Package dimensions	mm	340x340x50	340x340x180		
Mounting	-	fast clip-on			
Conformity/Certifications	-	CE			

* 0.5-2.5mm²

Versions				
UL-code ending			U	-
EMC-code ending			X_MPX	
Accessories				
Filter mat, standard type			ATVF5_MPX	
Filter mat, high efficiency			ATVF5X_MPX	
Thermostat 0-60°C, NO contact		-	THV2_MPX	
Hood for IP56			HPS325U	

