

# LEDLAMP 32

## SLIM, HIGH EFFICIENCY ENCLOSURE LED LAMP WITH MOTION SENSOR

Wide voltage range from 20VDC up to 265VAC in a single model.  
 Spring terminal. More units can be connected together in a chain.  
 Fixing clips in each model permit to rotate the lamp according to lighting needs.  
 Magnet fixing or screw fixing. Motion sensor or switch ON/OFF available.



SPRING TERMINAL



MOTION SENSOR OR ON / OFF SWITCH



CLIP FIXING WITH MAGNET OR SCREW



ORIENTABLE

Features	Unit	LEDLAMP3200_MPX	LEDLAMP3210_MPX
Power supply	V/Hz	24-48 VDC / 100-240 VAC 50-60 Hz	
Luminosity	Lm	400	
Lamp type	-	LED	
Power consumption	W	2,5	
Service life (@ 20°C)	hr	60.000	
Switch	-	on/off switch	Motion sensor*
Electrical connection	-	2-poles spring terminals **	
Casing	-	Plastic	
Protection degree / Class	-	IP20 / Class II	
Operating temperature	°C (°F)	-30 / +60 (-22 / +140)	
Storage temperature	°C (°F)	-40 / +85 (-40 / +185)	
Mounting	-	screw fixing	screw fixing
Installation position	-	Variable	
Dimensions	mm	Ø32x345	
Weight (with packaging)	kg	0.155 (0.205)	0.155 (0.205)
Package dimensions	mm	415x50x43	
Conformity/Certifications	-	CE,  File n° E301228	

\* 5min switched on after last detection

\*\* 0.5-2.5mm

