

# DES-PDM Q

## Cable entry plates with internal frame

- ▶ For several number of non-terminated cables in a limited space
- ▶ High retaining force thanks to the double membrane
- ▶ Cost efficient solution
- ▶ High IP grade (IP65-66)




| Model / Code      | Cable nr.<br>- Ø cables [mm]                                       | Dimensions [mm] |       | Pcs / pack |
|-------------------|--------------------------------------------------------------------|-----------------|-------|------------|
|                   |                                                                    | Cut-out         | Plate |            |
| DES-PDM-Q-13G_MPX | 8 - 2.8 / 6.5<br>4 - 4.6 / 10.2<br>1 - 14.5 / 22                   | 46 x 46         | 74x60 | 10         |
| DES-PDM-Q-17G_MPX | 10 - 2.8 / 6.5<br>4 - 4.6 / 10.2<br>2 - 6.8 / 12<br>1 - 8.6 / 16.2 |                 |       |            |
| DES-PDM-Q-25G_MPX | 25 - 2.8 / 6.5                                                     |                 |       |            |
| DES-PDM-Q-13B_MPX | 8 - 2.8 / 6.5<br>4 - 4.6 / 10.2<br>1 - 14.5 / 22                   | 46 x 46         | 74x60 | 10         |
| DES-PDM-Q-17B_MPX | 10 - 2.8 / 6.5<br>4 - 4.6 / 10.2<br>2 - 6.8 / 12<br>1 - 8.6 / 16.2 |                 |       |            |
| DES-PDM-Q-25B_MPX | 25 - 2.8 / 6.5                                                     |                 |       |            |

The DES-PDM Q is an innovative alternative to standard cable glands on electrical, electronic and telecommunication cabinets and equipment.

The cable is pushed through the front membrane, whilst the second membrane increases the strain relief and liquid resistance.

Double membrane



### Technical data

**Material:** TPE

**Flammability:** self-extinguishing acc. to UL94-V0

**Temperature:** -40°C... +105°C (static)

**Features:** halogens and silicones free

### Related products

Hydraulic punch driver HY360

### Dimensions [mm]

