

SPG



DES insert - large

- ▶ SPG: inserts for **pre-terminated cables** from 17 to 35 mm in diameter
- ▶ SPG K0: inserts for **non-terminated cables**
- ▶ "Blind" version available
- ▶ Grey and black colours available
- ▶ UL94V0 for both colours



SPG K0



Model / Code	Ø Cable [mm]	Model / Code	Pcs / pack
 SPG-0G_MPX	"blind"	 SPG-0B_MPX	10
SPG-K0G_MPX	"blind" pierceable Ø max. 32	SPG-K0B_MPX	
SPG-17G_MPX	17-18	SPG-17B_MPX	
SPG-18G_MPX	18-19	SPG-18B_MPX	
SPG-19G_MPX	19-20	SPG-19B_MPX	
SPG-20G_MPX	20-21	SPG-20B_MPX	
SPG-21G_MPX	21-22	SPG-21B_MPX	
SPG-22G_MPX	22-23	SPG-22B_MPX	
SPG-23G_MPX	23-24	SPG-23B_MPX	
SPG-24G_MPX	24-25	SPG-24B_MPX	
SPG-25G_MPX	25-26	SPG-25B_MPX	
SPG-26G_MPX	26-27	SPG-26B_MPX	
SPG-27G_MPX	27-28	SPG-27B_MPX	
SPG-28G_MPX	28-29	SPG-28B_MPX	
SPG-29G_MPX	29-30	SPG-29B_MPX	
SPG-30G_MPX	30-31	SPG-30B_MPX	
SPG-31G_MPX	31-32	SPG-31B_MPX	
SPG-32G_MPX	32-33	SPG-32B_MPX	
SPG-33G_MPX	33-34	SPG-33B_MPX	
SPG-34G_MPX	34-35	SPG-34B_MPX	

The SPG inserts enable several cables from 17 to 35 mm in diameter to be installed in the DES splittable frames.

Technical data

Material: TPE

Flammability: self-extinguishing acc. to UL94-V0

Temperature: -40°C... +110°C (static)

Features: halogens and silicones free

Related products

DES 24 DES PRED 63

DES 16 DES PRED 90-50

DES 10

DES Q

