

SPP

DES inserts - small: single, double and quadruple

- ▶ Inserts for cables from 2 to 16 mm in diameter
- ▶ “Blind” version available
- ▶ Grey and black colours available
- ▶ UL94V0 for both colours



The SPP inserts enable several cables from 2 to 16mm in diameter to be installed in the DES

The 2X and 4X versions enable multiple cables to be installed.

Technical data

Material: TPE

Flammability: self-extinguishing acc. to UL94-V0

Temperature: -40°C... +110°C (static)

Features: halogens and silicones free

Related products

- DES 24 DES L5 DES PRED
- DES 16 DES L4 DES PRED 90
- DES 10 DES L3 DES CLICK
- DES Q DES L2

Model / Code	Ø Cable [mm]	Model / Code	Pcs / pack
SPP-0G_MPX	“blind”	SPP-0B_MPX	10
SPP-2G_MPX	2-3	SPP-2B_MPX	
SPP-3G_MPX	3-4	SPP-3B_MPX	
SPP-4G_MPX	4-5	SPP-4B_MPX	
SPP-5G_MPX	5-6	SPP-5B_MPX	
SPP-6G_MPX	6-7	SPP-6B_MPX	
SPP-7G_MPX	7-8	SPP-7B_MPX	
SPP-8G_MPX	8-9	SPP-8B_MPX	
SPP-9G_MPX	9-10	SPP-9B_MPX	
SPP-10G_MPX	10-11	SPP-10B_MPX	
SPP-11G_MPX	11-12	SPP-11B_MPX	
SPP-12G_MPX	12-13	SPP-12B_MPX	
SPP-13G_MPX	13-14	SPP-13B_MPX	
SPP-14G_MPX	14-15	SPP-14B_MPX	
SPP-15G_MPX	15-16	SPP-15B_MPX	
SPP-16G_MPX	16	SPP-16B_MPX	
SPP-2x2G_MPX	2X2	SPP-2x2B_MPX	10
SPP-2x3G_MPX	2X3	SPP-2x3B_MPX	
SPP-2x4G_MPX	2X4	SPP-2x4B_MPX	
SPP-2x5G_MPX	2X5	SPP-2x5B_MPX	
SPP-2x6G_MPX	2X6	SPP-2x6B_MPX	
SPP-2x7G_MPX	2X7	SPP-2x7B_MPX	
SPP-2x8G_MPX	2X8	SPP-2x8B_MPX	
SPP-4x2G_MPX	4X2	SPP-4x2B_MPX	10
SPP-4x3G_MPX	4X3	SPP-4x3B_MPX	
SPP-4x4G_MPX	4X4	SPP-4x4B_MPX	
SPP-4x5G_MPX	4X5	SPP-4x5B_MPX	
SPP-4x6G_MPX	4X6	SPP-4x6B_MPX	

