



## SPP K

## DES inserts with extended range - non split

- Extended range inserts for non-terminated cables
- ▶ Diameters from 2.5 to 14 mm
- ► "Blind" insert pierceable available
- ► Grey and black colours available
- ▶ UL94V0 for both colours

| Model /<br>Code | Ø Cable<br>[mm] | Model /<br>Code | Pcs<br>/ pack |
|-----------------|-----------------|-----------------|---------------|
| •               |                 |                 |               |
| SPP-K0G_MPX     | senza foro      | SPP-K0B_MPX     |               |
| SPP-K1G_MPX     | 2.5/7           | SPP-K1B_MPX     |               |
| SPP-K2G_MPX     | 5/10            | SPP-K2B_MPX     | 10            |
| SPP-K3G_MPX     | 7.5/11.5        | SPP-K3B_MPX     |               |
| SPP-K4G_MPX     | 10/14           | SPP-K4B_MPX     |               |

The SPP K inserts enable non-terminated cables to be accommodated in the DES splittable frames. Each insert has an extended range. The "blind" insert, properly pierced, enables cables from 1 to 16mm in diameter to pass through the frame.

## Technical data

Material: TPE

Flammability: self-extinguishing acc. to

UL94-V0

Temperature: -40°C... +110°C (static)

Features: halogens and silicones free

## Related products

DES 24 DES L5 DES PRED DES 16 DES L4 DES PRED

90

DES 10 DES L3 DES CLICK

DES Q DES L2





