

SPP

Jointes passe-câbles, simples, doubles et quadruples

- Joints fendus passe-câbles pour câbles de diamètre de 2 à 16mm
- Disponible modèle sans perçage et joint bouchon
- Couleurs grise et noire
- UL94-V0 pour les 2 couleurs



Les joints passe-câbles fendus de la série SPP permettent de placer des câbles de 2 à 16 mm de diamètre à l'intérieur des passes câbles divisibles de la série DES. Les versions 2X et 4X sont indiquées pour augmenter le nombre de câbles dans les cadres.

Caractéristiques

Matériau: Elastomère thermoplastique (TPE)



Inflammabilité: autoextinguible suivant UL94-V0 (gris/noir)

Température: -40°C... +110°C (statique)

Propriété: sans halogènes, sans silicone

Accessoires

DES 24 DES L5 DES PRED
DES 16 DES L4 DES PRED 90
DES 10 DES L3 DES CLICK
DES Q DES L2



Type/ Code	Ø Trou [mm]	Type/ Code	Cond.
			
SPP-0G_MPX	senza foro	SPP-0B_MPX	10
SPP-2G_MPX	2-3	SPP-2B_MPX	
SPP-3G_MPX	3-4	SPP-3B_MPX	
SPP-4G_MPX	4-5	SPP-4B_MPX	
SPP-5G_MPX	5-6	SPP-5B_MPX	
SPP-6G_MPX	6-7	SPP-6B_MPX	
SPP-7G_MPX	7-8	SPP-7B_MPX	
SPP-8G_MPX	8-9	SPP-8B_MPX	
SPP-9G_MPX	9-10	SPP-9B_MPX	
SPP-10G_MPX	10-11	SPP-10B_MPX	
SPP-11G_MPX	11-12	SPP-11B_MPX	
SPP-12G_MPX	12-13	SPP-12B_MPX	
SPP-13G_MPX	13-14	SPP-13B_MPX	
SPP-14G_MPX	14-15	SPP-14B_MPX	
SPP-15G_MPX	15-16	SPP-15B_MPX	
SPP-16G_MPX	16	SPP-16B_MPX	
			
SPP-2x2G_MPX	2X2	SPP-2x2B_MPX	10
SPP-2x3G_MPX	2X3	SPP-2x3B_MPX	
SPP-2x4G_MPX	2X4	SPP-2x4B_MPX	
SPP-2x5G_MPX	2X5	SPP-2x5B_MPX	
SPP-2x6G_MPX	2X6	SPP-2x6B_MPX	
SPP-2x7G_MPX	2X7	SPP-2x7B_MPX	
SPP-2x8G_MPX	2X8	SPP-2x8B_MPX	
			
SPP-4x2G_MPX	4X2	SPP-4x2B_MPX	10
SPP-4x3G_MPX	4X3	SPP-4x3B_MPX	
SPP-4x4G_MPX	4X4	SPP-4x4B_MPX	
SPP-4x5G_MPX	4X5	SPP-4x5B_MPX	
SPP-4x6G_MPX	4X6	SPP-4x6B_MPX	