

SKINDICHT® BL-M



Benefits

- For closing pre-threaded holes

Application range

- Machine and equipment manufacturing
- Electric motor manufacturing

Product features

- Assembling with screwdriver

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC000032 ETIM 5.0/6.0 Class-Description: Plug for cable screw gland
	Certifications UL pending
	On request Fitted with FKM O-ring (-20°C to +200°C)
	Material Body: nickel-plated brass O-ring: NBR
	Protection rating IP 54 IP 68 (with O-ring)
	Temperature range With O-ring: -20°C to +100°C Without O-ring: -60°C to +200°C

Article number	Article designation / size	Overall length C mm	Thread length D mm	Outer Ø (mm)	Pieces / PU
SKINDICHT® BL-M					
BL-M-M12_MPX	M 12 x 1,5	7.5	5	14.0	100
BL-M-M16_MPX	M 16 x 1,5	8.0	5	18.0	100
BL-M-M20_MPX	M 20 x 1,5	9.5	6	22.0	100
BL-M-M25_MPX	M 25 x 1,5	11.0	7	28.0	100
BL-M-M32_MPX	M 32 x 1,5	12.0	8	35.0	50
BL-M-M40_MPX	M 40 x 1,5	13.0	9	44.0	25
BL-M-M50_MPX	M 50 x 1,5	15.0	9	54.0	10
BL-M-M63_MPX	M 63 x 1,5	16.0	10	70.0	10
BL-M-M75_MPX	M 75 x 1,5	17.0	11	80.0	1
SKINDICHT® BL-M con O-ring					
BL-M-M12-OR_MPX	M 12 x 1,5	7.5	5	14.0	100
BL-M-M16-OR_MPX	M 16 x 1,5	8.0	5	18.0	100
BL-M-M20-OR_MPX	M 20 x 1,5	9.5	6	22.0	100
BL-M-M25-OR_MPX	M 25 x 1,5	11.0	7	28.0	100
BL-M-M32-OR_MPX	M 32 x 1,5	12.0	8	35.0	50
BL-M-M40-OR_MPX	M 40 x 1,5	13.0	9	44.0	25
BL-M-M50-OR_MPX	M 50 x 1,5	15.0	9	54.0	10
BL-M-M63-OR_MPX	M 63 x 1,5	16.0	10	70.0	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.