

SKINDICHT® HYGIENIC BL-M















INFO

- Ideal for hygienic critical areas resistant, edge-free, robust and reliable
- No gaps, voids or outer lying thread
 so no risk of contamination of food machines, facilities or components

Benefits

- · For closing pre-threaded holes
- · Assembling with a wrench

Application range

- Food machinery, equipment and components
- · For use in product zone
- · Pharmaceutical industry

Norm references / Approvals

- NSF/ANSI 169
 Hygienic design for machinery and components
- ECOLAB® Industry standard in the field of professional cleaning and disinfection in the food and beverage industry

- FDA 21 CFR 177.2600
 Special sealing element for food and beverage industry in North America
- DIN EN 1672-2 Guideline for the design of machinery
- DIN EN ISO 14159
 Security of machinery Hygienic requirements for the design of machinery

Product Make-up

- Material and shape provide an easy and safe cleaning
- By the blue coloring of the sealing material clearly distinguishable from foodstuffs
- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Technical data

Classification ETIM 5/6

ETIM 5.0/6.0 Class-ID: EC000032 ETIM 5.0/6.0 Class-Description: Plug for cable screw gland



Material Body: stainless steel - V4A (1.4404 / 316L)

Sealing: special elastomer (FKM)

Protection rating



IP 68 - 10 bar
Temperature range

-20°C to +100°C

Article number	Article designation / size	SW wrench size mm	Overall length C mm	Thread length D mm	Outer Ø (mm)	Pieces / PU
SKINDICHT® HYGIENIC BL-M						
BL-M-HYG-M12-OR_MPX	M 12 x 1,5	16	16.9	6.5	18.8	5
BL-M-HYG-M16-OR_MPX	M 16 x 1,5	20	17.9	7	22.8	5
BL-M-HYG-M20-OR_MPX	M 20 x 1,5	24	19.9	8	26.8	5
BL-M-HYG-M25-OR_MPX	M 25 x 1,5	29	20.7	8	31.8	5

Photographs and graphics are not to scale and do not represent detailed images of the respective products.