

## SKINDICHT® SM-M INOX



### Application range

- Used when a gland has to be countered, or in through-holes on thin-walled housings


### Product Make-up


- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444


### INFO

- Metric threaded, stainless steel counter nut

### Technical data


**Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC000940  
 ETIM 5.0/6.0 Class-Description:  
 Locknut for cable screw gland


**Material**  
 Stainless steel 303


**Temperature range**  
 -60°C to +200°C

Article number	Article designation / size	Thickness (mm)	SW wrench size mm	Outer Ø (mm)	Pieces / PU
<b>SKINDICHT® SM-M INOX</b>					
SM-M-M12-INOX_MPX	M 12 x 1,5	2.8	17	16.5	10
SM-M-M16-INOX_MPX	M 16 x 1,5	2.8	19	20.9	10
SM-M-M20-INOX_MPX	M 20 x 1,5	3.0	24	26.7	10
SM-M-M25-INOX_MPX	M 25 x 1,5	3.5	30	33.0	10
SM-M-M32-INOX_MPX	M 32 x 1,5	4.0	36	39.0	10
SM-M-M40-INOX_MPX	M 40 x 1,5	5.0	46	50.0	10
SM-M-M50-INOX_MPX	M 50 x 1,5	5.0	55	60.0	10
SM-M-M63-INOX_MPX	M 63 x 1,5	6.0	70	78.0	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.