

SKINDICHT® SM-M / SKINDICHT® SM-PE-M



SKINDICHT® SM-M

Benefits

SKINDICHT® SM-PE-M

- Cutting edges cut through the insulating layer, thus guaranteeing an optimum EMC contact
- Suitable for all metric glands used in earthing and EMC applications

Application range

SKINDICHT® SM-M

- Used when a gland has to be countered, or in through-holes on thin-walled housings

SKINDICHT® SM-PE-M

- For lacquered, anodised or powder-coated housings.

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

SKINDICHT® SM-PE-M

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC000940 ETIM 5.0/6.0 Class-Description: Locknut for cable screw gland
	Material Nickel-plated brass
	Temperature range -60°C to +200°C

Article number	Article designation / size	Thickness (mm)	SW wrench size mm	Outer Ø (mm)	Pieces / PU
SKINDICHT® SM-M					
SM-M-M6_MPX	M 6 x 1	3.2	10	11.1	100
SM-M-M8_MPX	M 8 x 1	4.0	13	14.4	100
SM-M-M10_MPX	M 10 x 1	5.0	17	19.1	100
SM-M-M12_MPX	M 12 x 1,5	3.0	15	16.5	100
SM-M-M16_MPX	M 16 x 1,5	3.0	19	20.9	100
SM-M-M20_MPX	M 20 x 1,5	3.5	24	26.4	100
SM-M-M25_MPX	M 25 x 1,5	4.0	30	33.0	100
SM-M-M32_MPX	M 32 x 1,5	4.0	36	39.6	100
SM-M-M40_MPX	M 40 x 1,5	5.0	46	50.6	50
SM-M-M50_MPX	M 50 x 1,5	5.0	60	65.0	50
SM-M-M63_MPX	M 63 x 1,5	5.0	70	77.0	25
SM-M-M75_MPX	M 75 x 1,5	8.0	85	95.0	1
SM-M-M90_MPX	M 90 x 2	10.0	102	114.0	1
SM-M-M110_MPX	M 110 x 2	12.0	124	135.0	1
SKINDICHT® SM-PE-M					
SM-PE-M-M12_MPX	M 12 x 1,5	4.7	15	17.3	100
SM-PE-M-M16_MPX	M 16 x 1,5	4.7	19	21.9	100
SM-PE-M-M20_MPX	M 20 x 1,5	4.7	24	27.7	100
SM-PE-M-M25_MPX	M 25 x 1,5	5.2	30	34.6	50
SM-PE-M-M32_MPX	M 32 x 1,5	5.7	36	41.5	50
SM-PE-M-M40_MPX	M 40 x 1,5	6.5	46	53.1	25
SM-PE-M-M50_MPX	M 50 x 1,5	6.5	60	69.3	10
SM-PE-M-M63_MPX	M 63 x 1,5	7.0	70	80.8	10
SM-PE-M-M75_MPX	M 75 x 1,5	8.0	85	95.0	1
SM-PE-M-M72_MPX	M 72 x 2	10.0	85	98.0	1
SM-PE-M-M90_MPX	M 90 x 2	10.0	102	114.0	1
SM-PE-M-M110_MPX	M 110 x 2	12.0	124	135.0	1

Photographs and graphics are not to scale and do not represent detailed images of the respective products.